

DPM2-52 & DPM-52 TRACKED AERIAL LIFT

TELESCOPIC ARTICULATING PERSONNEL OR MATERIAL HANDLING AERIAL LIFT

DUR-A-LIFT®



TREK THROUGH ROUGH TERRAIN. THIS LIFT IS ABLE TO:

- **CLIMB A 40 DEGREE SLOPE**
- **EASILY MANEUVER OVER UNEVEN GROUND**
- **AND EVEN WADE THROUGH 3 FEET OF WATER**

**SINGLE PERSON
MATERIAL HANDLING
OR
DOUBLE PERSON
PERSONNEL**

**AVAILABLE WITH A
TOP (DPM2) OR
SIDE (DPM) MOUNTED
JIB AND WINCH**



**22" BASKET ELEVATOR
AVAILABLE ON DPM2**

sales@dur-a-lift.com
www.dur-a-lift.com

Dur-A-Lift Inc., P.O. Box 31, George, Iowa 51237
(877) 4-DURALIFT (877) 438-7254 | Fax: (712) 475-2809

DPM2-52 & DPM-52

TRACKED AERIAL LIFT

TELESCOPIC ARTICULATING PERSONNEL OR MATERIAL HANDLING AERIAL LIFT



STANDARD

- Proportional controls
- Lower override controls
- Engine start/stop from basket
- **Basket access from ground**
- Compensated upper boom
- Insulated Category "C"
- Hydraulic basket leveling
- Continuous rotation
- High electrical resistant joystick controls

Brought to you in connection with



DPM2-52MH & DPM-52MH

MH - MATERIAL HANDLING

- Up to 1000# jib and winch
- **Upper and lower winch control**
- 400# basket capacity
- 24" X 30" fiberglass basket
- **180° basket rotator**

DPM2-52DU & DPM-52DU

DU - DUAL CONFIGURATION: DUAL PERSON OR MATERIAL HANDLING

- Up to 1000# jib and winch
- **Upper and lower winch control**
- 550# basket capacity when not using winch
- 400# basket capacity when using winch
- 24" X 42" fiberglass basket
- 100° basket rotator

OPTIONS

- **22" basket elevator** DPM2
- Basket liner for fiberglass baskets
- Tool circuits
- Fiberglass main and articulating booms
- D.C. backup system
- 180° basket rotator


This aerial lift is sold and serviced by:

SPECIFICATIONS


	DPM2-52	DPM-52
Height to bottom of platform*	54'	52'
Working height*	59'	57'
Side reach	31' 6"	31' 6"
Stowed travel height	9' 3"	9' 3"
Basket capacity (MH MODELS)	400#	400#
Basket capacity using jib (DU MODELS)	400#	400#
Basket capacity not using jib (DU MODELS)	550#	550#
Approximate weight (lift only)	4400#	4400#
Articulated arm travel	0 to 75	0 to 75
Main boom travel	-30 to 75	-30 to 75
Extension travel	120"	120"

Dur-A-Lift Inc. reserves the right to improve models and change specifications without notice or obligation. Dur-A-Lift equipment meets or exceeds all applicable ANSI Standards as of the date of manufacture.

*Achievable with optional 22" basket elevator




Level lift on 8 degree front/rear slope



Level lift on 10 degree side slope



Side slope capacity of -15 degrees horizontal



Maximum water depth of 3 feet



sales@dur-a-lift.com
www.dur-a-lift.com

Dur-A-Lift Inc., P.O. Box 31, George, Iowa 51237
(877) 4-DURALIFT (877) 438-7254 | Fax: (712) 475-2809