

**DUR-A-LIFT**<sup>®</sup>

# MODEL GUIDE



**FIND MORE ONLINE**  
[WWW.DUR-A-LIFT.COM/BUCKET-TRUCK](http://WWW.DUR-A-LIFT.COM/BUCKET-TRUCK)

**DUR-A-LIFT**<sup>®</sup>

DUR-A-LIFT INC., 2002 KINGBIRD AVE., GEORGE, IOWA 51237  
[WWW.DUR-A-LIFT.COM](http://WWW.DUR-A-LIFT.COM) | [SALES@DUR-A-LIFT.COM](mailto:SALES@DUR-A-LIFT.COM) | 1-877-4DURALIFT  
2023-08-MODEL-GUIDE-01

# SERIES AT A GLANCE

## TELESCOPIC ARTICULATED

### DLT2 SERIES

- Working height up to 67'
- Material handling or 2-person basket options
- Top-mounted jib lifts up to 1000#, optional
- Basket elevator option; 180-degree basket rotator
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DLT2); non-insulated (DLT2S)



### DPM3 SERIES

- Working height up to 60'8"
- 36" X 60" bottom-mount, aluminum basket
- Auxiliary winch lifts up to 150#, optional
- 180-degree basket rotator
- Insulated, Cat. D (DPM3) or non-insulated (DPM3S)



### DPM2 SERIES

- Working height up to 59'
- Material handling or 2-person basket options
- Top-mounted jib lifts up to 1000#, optional
- Basket elevator option; 180-degree basket rotator
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DPM2); non-insulated (DPM2S)



### DPM SERIES

- Working height up to 57'
- Material handling or 2-person basket options
- Side-mounted jib lifts up to 1000#, optional
- 180-degree basket rotator; 3 basket styles
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DPM); non-insulated (DPMs)



### DTAX2 SERIES

- Working height up to 49'
- Up to 400# basket capacity
- Bottom-mount basket
- 180-degree basket rotator
- Fiberglass or aluminum basket options, 24"x24"
- Options available for use with 9' body
- Insulated, Cat. C & D (DTAX2); non-insulated (DTAX2S)



### DTA2 SERIES

- Working height up to 45'
- Up to 400# basket capacity
- End or side hung basket
- Basket rotator option
- Fiberglass or aluminum basket options, 24"x24"
- Options available for use with 9' body
- Insulated, Cat. C & D (DTA2); non-insulated (DTA2S)

## TELESCOPIC



### DPM2-32

- Telescopic DPM2
- Working height up to 39'



### DPM-32

- Telescopic DPM
- Working height up to 37'



### DTX2 SERIES

- Telescopic DTAX2
- Working height up to 39'



### DT2 SERIES

- Telescopic DTA2
- Working height up to 36'

## SPECIALTY



### CABLE PLACER

400# side pull, 50# down pull; operates in stationary and mobile mode



### URBAN FORESTRY

Telescopic articulating bucket truck with aluminum chipper box



### TRACKED AERIAL

Great option for those who work in areas with wet or uneven terrain.

## BUCKET VAN



### DVS-29

Telescopic aerial lift mounted on a cutaway chassis; tons of storage



### DVT-29

Telescopic aerial lift mounted on a transit cargo van; under 10,000 GVWR



### DO SERIES

Articulating overcenter; working height up to 41'; side reach to 30'4"

# MODELS AT A GLANCE

TELESCOPIC ARTICULATED										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DLT2-60*	DU	67'	39'2"	134"	12'	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DLT2S)	Top-mounted jib, 1000#
	MH	67'	39'2"	134"	12'	24"x30"	400	Cat. C & D	Yes (DLT2S)	Top-mounted jib, 1000#
	DP	67'	39'2"	134"	12'	24"x42"	600	Cat. C & D	Yes (DLT2S)	No
DPM3-56	AW <sup>CF</sup>	60'8"	29'7"	120"	11'6"	36"x60"	400/550 <sup>1</sup>	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	60'8"	29'7"	120"	11'6"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-51	AW	56'6"	30'6"	120"	10'5"	36"x60"	400/550 <sup>1</sup>	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	56'6"	30'6"	120"	10'5"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-44	AW	49'5"	31'3"	120"	10'5"	36"x60"	400/550 <sup>1</sup>	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	49'5"	31'3"	120"	10'5"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-40	AW	45'7"	27'3"	96"	10'5"	36"x60"	400/550 <sup>1</sup>	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	45'7"	27'3"	96"	10'5"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM2-52*	DU <sup>CF</sup>	59'	31'6"	120"	11'8"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	59'	31'6"	120"	11'8"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	59'	31'6"	120"	11'8"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-47*	DU <sup>CF</sup>	54'	31'6"	120"	10'5"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	54'	31'6"	120"	10'5"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	54'	31'6"	120"	10'5"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-40*	DU	47'	31'6"	120"	10'6"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	47'	31'6"	120"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	47'	31'6"	120"	10'6"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-36*	DU	43'	27'6"	96"	10'6"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	43'	27'6"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	43'	27'6"	96"	10'6"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM-52	DU	57'	31'6"	120"	11'8"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	57'	31'6"	120"	11'8"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	57'	31'6"	120"	11'8"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-47	DU	52'	31'6"	120"	10'5"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	52'	31'6"	120"	10'5"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	52'	31'6"	120"	10'5"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-40	DU	45'	31'6"	120"	10'6"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	45'	31'6"	120"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	45'	31'6"	120"	10'6"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-36	DU	41'	27'6"	96"	10'6"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	41'	27'6"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	41'	27'6"	96"	10'6"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No

<sup>CF</sup> CUSTOMER FAVORITE

CONTINUED ON NEXT PAGE

- **Printable copies:** [bit.ly/DAL-Model-Guide](https://bit.ly/DAL-Model-Guide)
- **View it online:** [dur-a-lift.com/bucket-truck-guide/#models](https://dur-a-lift.com/bucket-truck-guide/#models)



DUR-A-LIFT INC., 2002 KINGBIRD AVE., GEORGE, IOWA 51237  
 WWW.DUR-A-LIFT.COM | SALES@DUR-A-LIFT.COM | 1-877-4DURALIFT  
 2023-08-MODEL-GUIDE-03

TELESCOPIC ARTICULATED										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DTAX2-	44	49'	30'	122.5"	10'	24"x24"	350	Cat. C & D	Yes (DTAX2S)	No
	42 <sup>CF</sup>	47'	28'	110.5"	10'	24"x24"	400	Cat. C & D	Yes (DTAX2S)	No
	39	44'	28'	110.5"	10'	24"x24"	400	Cat. C & D	Yes (DTAX2S)	No
DTA2-	40 <sup>CF</sup>	45'	28'6" <sup>2</sup>	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA2S)	No
	38	44'	27'6" <sup>2</sup>	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA2S)	No
	35	41'	27'8" <sup>2</sup>	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA2S)	No
TELESCOPIC										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DTX2-	34	39'	25'2"	122.5"	10'3"	24"x24"	350	Cat. C & D	Yes (DTX2S)	No
	32	37'	23'2"	110.5"	10'3"	24"x24"	400	Cat. C & D	Yes (DTX2S)	No
DT2-	31	36'	22'8" <sup>3</sup>	122.5"	10'6"	24"x24"	350	Cat. D	Yes (DT2S)	No
	29	34'	20'8" <sup>3</sup>	110.5"	10'6"	24"x24"	400	Cat. D	Yes (DT2S)	No
DPM2-	32DU	39'*	25'4"	120"	10'8"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	32MH	39'*	25'4"	120"	10'8"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	32DP	39'*	25'4"	120"	10'8"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM-	32DU	37'	25'4"	120"	10'8"	24"x42"	400/550 <sup>1</sup>	Cat. C & D	Yes (DPM5)	Side-mounted jib, 1000#
	32MH	37'	25'4"	120"	10'8"	24"x30"	400	Cat. C & D	Yes (DPM5)	Side-mounted jib, 1000#
	32DP	37'	25'4"	120"	10'8"	24"x48"	600	Cat. C & D	Yes (DPM5)	No
BUCKET VAN										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DVS-	29	34'	21'	108"	10'1"	24"x24"	350	No	Standard	No
DVT-	29 <sup>CF</sup>	34'	21'2"	108"	9'6"	24"x24"	350	No	Standard	No
ARTICULATED										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DO-	36	41'	30'4"	—	9'8"	24"x24"	350	Cat. D	Yes (DOS)	No
	32	37'	26'4"	—	9'8"	24"x24"	350	Cat. D	Yes (DOS)	No
SPECIALTY										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
CABLE PLACER DCP-	36 <sup>CF</sup>	41'	26'6"	110.5"	10'1"	24"x30"	350	No	Standard	400# side pull, 50# down pull
	29	34'	22'6"	110.5"	10'5"	24"x30"	350	No	Standard	400# side pull, 50# down pull
URBAN FORESTRY DPM2-	53	60'*	31'6"	120"	12'4"	24"x30"	600	Cat. C & D	Yes (DPM2S)	No
URBAN FORESTRY DTAX-	45 <sup>CF</sup>	50'	30'	122.5"	11'3"	24"x24"	350	Cat. C & D	Yes (DTAX2S)	No
	40	45'	30'	110.5"	11'2"	24"x24"	400	Cat. C & D	Yes (DTAX2S)	No

NOTE: Stowed travel height may vary by chassis.

\* Maximum working height achieved with optional basket elevator

1 - Basket capacity with jib in use / jib not in use

2 - End-hung basket or basket with rotator. Subtract 2' for side-hung basket.

3 - Side-hung basket. Add 1'10" for end-hung.

BASKET STYLE NAMING GUIDE:

DU - Double configuration. Can be used as single person material handling or double person

MH - Single person, material handling.

DP - Double person, personnel.

AW - With auxiliary winch.

SW - No auxiliary winch.