

DUR-A-LIFT®

MODEL GUIDE



FIND MORE ONLINE
DUR-A-LIFT.COM/BUCKET-TRUCK

SERIES AT A GLANCE

TELESCOPIC ARTICULATING

DLT2 SERIES

- Working height up to 67'
- Material handling or 2-person basket options
- Top-mounted jib lifts up to 1000#, optional
- Basket elevator option; 180-degree basket rotator
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DLT2); non-insulated (DLT2S)



DPM3 SERIES

- Working height up to 60'8"
- 36" X 60" bottom-mount, aluminum basket
- Auxiliary winch lifts up to 150#, optional
- 180-degree basket rotator
- Insulated, Cat. D (DPM3) or non-insulated (DPM3S)



DPM2 SERIES

- Working height up to 59'
- Material handling or 2-person basket options
- Top-mounted jib lifts up to 1000#, optional
- Basket elevator option; 180-degree basket rotator
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DPM2); non-insulated (DPM2S)



DPM SERIES

- Working height up to 57'
- Material handling or 2-person basket options
- Side-mounted jib lifts up to 1000#, optional
- 180-degree basket rotator; 3 basket styles
- Fiberglass or aluminum basket options
- Insulated, Cat. C & D (DPM); non-insulated (DPM3S)



DTAX2 SERIES

- Working height up to 49'
- Up to 400# basket capacity
- Bottom-mount basket
- 180-degree basket rotator
- Fiberglass or aluminum basket options, 24"x24"
- Options available for use with 9' body
- Insulated, Cat. C & D (DTAX2); non-insulated (DTAX2S)



DTA2 SERIES

- Working height up to 45'
- Up to 400# basket capacity
- End or side hung basket
- Basket rotator option
- Fiberglass or aluminum basket options, 24"x24"
- Options available for use with 9' body
- Insulated, Cat. C & D (DTA2); non-insulated (DTA2S)

TELESCOPIC



DPM2-32

- Telescopic DPM2
- Working height up to 39'



DPM-32

- Telescopic DPM
- Working height up to 37'



DTX2 SERIES

- Telescopic DTAX2
- Working height up to 39'



DT2 SERIES


- Telescopic DTA2
- Working height up to 36'

SPECIALTY




CABLE PLACER

400 pounds of side pull, 50 pounds of down pull; operates in mobile mode



URBAN FORESTRY

Telescopic articulating bucket truck with aluminum chipper box



TRACKED AERIAL

Great option for those who work in areas with wet or uneven terrain.



FIBER SPLICING AERIAL LIFT

Climate-controlled fiber splicing lab integrated with an aerial lift.



DVS-29

Telescopic aerial lift mounted on a cutaway chassis; tons of storage



DVT-29

Telescopic aerial lift mounted on a transit cargo van; under 10,000 GVWR

BUCKET VAN

MODELS AT A GLANCE

TELESCOPIC ARTICULATING, MATERIAL HANDLING OPTION										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DLT2-60	DU 	67'*	39'2"	134"	12'	24"x42"	400/550 ¹	Cat. C & D	Yes (DLT2S)	Top-mounted jib, 1000#
	MH	67'*	39'2"	134"	12'	24"x30"	400	Cat. C & D	Yes (DLT2S)	Top-mounted jib, 1000#
	DP	67'*	39'2"	134"	12'	24"x42"	600	Cat. C & D	Yes (DLT2S)	No
DPM3-56	AW 	60'8"	29'7"	120"	11'6"	36"x60"	400/550 ¹	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	60'8"	29'7"	120"	11'6"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-51	AW	56'6"	30'6"	120"	10'5"	36"x60"	400/550 ¹	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	56'6"	30'6"	120"	10'5"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-44	AW	49'8"	29'9"	96"	10'6"	36"x60"	400/550 ¹	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	49'8"	29'9"	96"	10'6"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM3-42	AW	47'8"	27'9"	96"	10'6"	36"x60"	400/550 ¹	Cat. D	Yes (DPM3S)	Auxiliary winch, 150#
	SW	47'8"	27'9"	96"	10'6"	36"x60"	600	Cat. D	Yes (DPM3S)	No
DPM2-52	DU 	59'*	31'6"	120"	11'8"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	59'*	31'6"	120"	11'8"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	59'*	31'6"	120"	11'8"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-47	DU 	54'*	31'6"	120"	10'5"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	54'*	31'6"	120"	10'5"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	54'*	31'6"	120"	10'5"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-40	DU 	47'*	30'3"	96"	10'6"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	47'*	30'3"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	47'*	30'3"	96"	10'6"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM2-38	DU	45'*	28'3"	96"	10'6"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	MH	45'*	28'3"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM2S)	Top-mounted jib, 1000#
	DP	45'*	28'3"	96"	10'6"	24"x42"	600	Cat. C & D	Yes (DPM2S)	No
DPM-52	DU	57'	31'6"	120"	11'8"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	57'	31'6"	120"	11'8"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	57'	31'6"	120"	11'8"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-47	DU	52'	31'6"	120"	10'5"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	52'	31'6"	120"	10'5"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	52'	31'6"	120"	10'5"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-40	DU	45'	30'7"	96"	10'6"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	45'	30'7"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	45'	30'7"	96"	10'6"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No
DPM-38	DU	43'	28'7"	96"	10'6"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	MH	43'	28'7"	96"	10'6"	24"x30"	400	Cat. C & D	Yes (DPM5S)	Side-mounted jib, 1000#
	DP	43'	28'7"	96"	10'6"	24"x48"	600	Cat. C & D	Yes (DPM5S)	No

 CUSTOMER FAVORITE

* Maximum working height achieved with optional basket elevator

CONTINUED ON NEXT PAGE

TELESCOPIC ARTICULATING, PERSONNEL										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DTAX2-	44	49'	30'	122.5"	10'	24"x24"	350	Cat. C & D	Yes (DTAX25)	No
	42 CF	47'	28'	110.5"	10'	24"x24"	400	Cat. C & D	Yes (DTAX25)	No
	39	44'	28'	110.5"	10'	24"x24"	400	Cat. C & D	Yes (DTAX25)	No
DTA2-	40 CF	45'	28'6" ²	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA25)	No
	38	44'	27'6" ²	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA25)	No
	35	41'	27'8" ²	110.5"	10'7"	24"x24"	400	Cat. C & D	Yes (DTA25)	No
TELESCOPIC										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DTX2-	34 CF	39'	25'2"	122.5"	10'3"	24"x24"	350	Cat. C & D	Yes (DTX25)	No
	32	37'	23'2"	110.5"	10'3"	24"x24"	400	Cat. C & D	Yes (DTX25)	No
DT2-	31	36'	22'8" ³	122.5"	10'6"	24"x24"	350	Cat. D	Yes (DT25)	No
	29	34'	20'8" ³	110.5"	10'6"	24"x24"	400	Cat. D	Yes (DT25)	No
DPM2-	32DU	39'*	25'4"	120"	10'8"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM25)	Top-mounted jib, 1000#
	32MH	39'*	25'4"	120"	10'8"	24"x30"	400	Cat. C & D	Yes (DPM25)	Top-mounted jib, 1000#
	32DP	39'*	25'4"	120"	10'8"	24"x42"	600	Cat. C & D	Yes (DPM25)	No
DPM-	32DU	37'	25'4"	120"	10'8"	24"x42"	400/550 ¹	Cat. C & D	Yes (DPM5)	Side-mounted jib, 1000#
	32MH	37'	25'4"	120"	10'8"	24"x30"	400	Cat. C & D	Yes (DPM5)	Side-mounted jib, 1000#
	32DP	37'	25'4"	120"	10'8"	24"x48"	600	Cat. C & D	Yes (DPM5)	No
BUCKET VANS										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
DVS-	29	34'	21'	108"	10'1"	24"x24"	350	No	Standard	No
DVT-	29 CF	34'	21'2"	108"	9'6"	24"x24"	350	No	Standard	No
SPECIALTY LIFTS										
MODEL		WORKING HEIGHT	SIDE REACH	EXT. BOOM	STOWED HEIGHT	BASKET SIZE	BASKET CAPACITY (#)	INSULATED OPTION	NON-INS. OPTION	MATERIAL HANDLING
FIBER SPLICING DTA2-	37	42'	26'5"	78"	12'	24"x24"	400	Cat. D	Yes (DTA25)	No
CABLE PLACER DCP-	36	41'	26'6"	110.5"	10'1"	24"x30"	350	No	Standard	400# side pull, 50# down pull
	29	34'	22'6"	110.5"	10'5"	24"x30"	350	No	Standard	400# side pull, 50# down pull
URBAN FORESTRY DPM2-	53 CF	60'*	31'6"	120"	12'4"	24"x30"	600	Cat. C & D	Yes (DPM25)	No
URBAN FORESTRY DTAX-	45	50'	30'	122.5"	11'3"	24"x24"	350	Cat. C & D	Yes (DTAX25)	No
	40	45'	30'	110.5"	11'2"	24"x24"	400	Cat. C & D	Yes (DTAX25)	No

NOTE: Stowed travel height may vary by chassis.

* Maximum working height achieved with optional basket elevator

1 - Basket capacity with jib in use / jib not in use

2 - End-hung basket or basket with rotator. Subtract 2' for side-hung basket.

3 - Side-hung basket. Add 1'10" for end-hung.

BASKET STYLE NAMING GUIDE:

DU - Double configuration. Can be used as single person material handling or double person

MH - Single person, material handling.

DP - Double person, personnel.

AW - With auxiliary winch.

SW - No auxiliary winch.

CF CUSTOMER FAVORITE